Certified deposit safe meeting renowned EN 1143-2 standard



ProGuard DT

BURGLARY-RESISTANT PROTECTION

Key Features

- ProGuard DT is a fully certified deposit safe, tested and approved in accordance with the European standard, EN 1143-2, in Grades DI and DII.
- Importantly, the EN 1143-2 certification means that insurance ratings are not affected by the addition of the deposit function to the safe.
- The deposit drawer is equipped with an anti-fishing device to prevent anyone reaching the contents of the safe through the drawer.
- Deposits are made into a safe built using the same technology as the ProGuard, which is certified in accordance with the European standard, EN 1143-1, for Grade II.
- ProGuard DT is constructed using a new composite material designed for strength and reduction in total weight. Less weight helps keep transportation and installation costs at a minimum.

- The three-way boltwork is constructed with solid steel bolts.
- For additional security, ProGuard DT is fitted with an active relocker and anti-drilling plates have been incorporated into the boltwork to resist burglary attempts.
- A Class A mechanical key lock or a Class B highsecurity electronic lock, approved in accordance with EN 1300, are both available as primary lock options for the safe. Electronic locks increase the level of security and prevent unauthorised access to the safe.
- Drawer trap fitted with a Class A key lock.
- ProGuard DT has a modern design with an ergonomic soft-touch handle.













Chubbsafes' policy is one of continuous improvement. Specifications may be subject to alteration from time to time without prior notice

Product Specifications

	External (mm)			Internal (mm)					
Model	Height	Width	Depth	Height	Width	Depth	Weight (kg)		Volume*
							Grade I	Grade II	(litres)
60	687	500	521	314	400	360	144	329	45
110	847	600	561	474	500	386	203	464	91
150	1052	600	561	659	500	386	242	554	127
200	1307	600	561	934	500	386	290	665	180

^{*=} Useable volume below deposit and anti-fishing device

Drawers internal dimensions (mm)							
Height	Wi model 60	Depth					
90	350	450	230				

Lock Options



Electronic Lock

The drawer trap is locked with a Class A key lock. The safe can be fitted with either a high-security electronic lock (Class B) or a key lock (Class A).

The primary lock on the safe can be complemented by a combination lock or both a key lock and electronic lock can be fitted.

All locks are tested by ECB•S and are certified in accordance with the EN 1300 standard.

ProGuard DT's high-security electronic lock – certified Class B by ECB•S – includes the following features:

- 1 master code, 1 supervisor code and 7 user codes.
- Time delay of up to 99 minutes between lock being operated and door being opened. Also equipped with time-delay override.
- Protective function to raise silent alarm if lock is being opened under duress.

Burglary Testing

ProGuard DT has been certified EN 1143-2 in Grades DI and DII by ECB•S¹. This fully graded burglary protection means that insurance

ratings for the safe are not effected by the drawer trap function.

A range of attack tools were used to test ProGuard DT's level of resistance, from basic tools to sophisticated thermal and electrical equipment.

¹ European Certification Board•Security Systems

Authorised dealer

