

SPECIFICATION SHEET: S010
SYSTEM 1600
MODULAR RANGE LOCKERS



Dimensions:

Height	Width	Depth
340 mm	300 mm	300 mm
340 mm	380 mm	380 mm

Strength and Security with Style

Sturdy Construction:	Door frame constructed from heavy gauge mild steel of press formed channel section.
Door Strength:	Two 'five knuckle' semi-concealed hinges.
Style:	Attractive and functional locker design.
Colour:	Automated paint plant ensures consistent high quality finish in a wide range of modern colours.

Detailed Product Specification

Nesting:	All Modular lockers are drilled in sides, tops and bottoms, to enable them to be bolted together into configurations to suit the user.
Construction:	Spot welded and pop riveted.
Material & Finish:	Mild steel-Powder Coated.
Door Frame Assembly:	Comprising two uprights manufactured from heavy gauge mild steel of press formed channel section; top and bottom cross members which are designed to create door stops. Spot welded construction produces a rigid frame enabling door clearances to be maintained in accordance with British Standard requirements. The top cross member is provided with a series of ventilation slots.
Doors:	Doors are attached to the right hand side of door frame upright with two 'five knuckle' semi-concealed hinges. Doors are fitted with a plastic escutcheon plate around the lock, which can also act as a name card/locker number holder. The inside of the door has a full length vertical 'stiffener' to provide greater rigidity. Two rubber buffers are fitted to the top and bottom corners of the door for quiet closure.
Locking:	Standard options are either 10 disc tumbler cam lock in mastered suite with two keys to each lock or, at no extra cost, a latch lock for the user's own padlock (recommended padlock shank dimensions 6 mm). Recommended padlocks are available from Helmsman.
Ventilation:	Ventilation is provided by a series of unique ventilation slots in the top cross member.
Paint Finish:	Five stage automatic degreasing and phosphating process to remove surface contamination. This base gives improved adhesion and humidity resistance. The powder is electrostatically applied prior to oven baking at the appropriate temperature.
Colour Range:	Standard locker frame Powder Coated colours is: "Ice". Standard door colours are: "Ice", "Black", "Rockpool", "Smoke", "White", "Skye", "Yellow", "Royale", "Forest" and "Cherry". The Helmsman general brochure illustrates these colours. Exact colour samples are available.

- OPTIONAL EXTRAS:** The following can be supplied at an additional cost and, if included, will be specified in the quotation.
- Shelf:** Shelf fitted at 195 mm height from the bottom of unit. Front edge has a 20 mm safety edge flange.
- Perforation:** Most parts of the locker can be perforated with the unique 'Helmsman' perforation profile (please refer to Information Sheet I008).
- Locker Numbering:**
- Number Label – Made of silver polyester, with a permanent, self-adhesive back. Numbers are printed in black and can comprise one to four digits including letters.
 - Number Plate – Made of laminated plastic, white numbers on black, numbers can comprise one to four digits including letters.
 - Number Discs – Laminated plastic 25 mm diameter, white numbers on black, numbers can comprise one to four digits. The disc is holed and a split key ring is provided.
- Plinths:** A special 50 mm high plinth is available to raise a Modular locker from the ground.
- Stands:** Groups of Modular lockers can be mounted on 760 mm high stands. The stands are constructed from 25 mm square section mild steel tube and finished as for the Modulares. For the 300 mm unit the stand is 1500 mm wide x 300 mm deep and will accommodate 5 Modular units wide. We recommend no more than 4 units high. For the 380 mm unit the stand is 1520 mm wide x 300 mm deep and will accommodate 4 Modular units. We recommend no more than 4 units high.
- Installation:** Helmsman offers a full installation service for its products.

Bespoke: We have the ability to customise our products to meet your requirement and space, providing solutions for awkward corners, uneven floors or even curved walls.

After-sales Service: All of our products are supported by the Helmsman Service team who provide technical advice, maintenance schemes, prompt delivery of replacement keys/parts and product refurbishment. Contact them on 01284 727633 or email service@helmsman.co.uk

- Health & Safety: Lockers must be firmly secured to wall or floor and fixed together in runs for safety purposes. If applicable, install in accordance with specific product instructions.
- All dimensions are nominal.
- To enable us to interpret your requirements accurately, please state at time of enquiry/order the choice of locker type, colour, locking and nesting arrangement and delivery requirement.
- The products described in this specification sheet herein are the subjects of patent, trademark, design and copyright protection or application thereof.
- In the interest of efficiency and service to our customers, the company reserves the right to modify the specifications of any of its products.

